GRESPANIA, S.A.

FICHA DE CARACTERÍSTICAS TÉCNICAS
TECHNICAL PROPIERTIES SHEET

REFERENCIA / CODE: **SAJONIA**

GRUPO / GROUP: BIa

RESISTENCIA A LOS AGENTES QUÍMICOS (Ácidos, bases, productos domésticos de limpieza)
CHEMICAL AGENTS RESISTANCE (Acids, bases, home cleaning products)

			CLASE / TYPE
Solución de ácido clorhídrico	*Chloridryc acid*	(UNE-EN ISO 10545-13)	GLA
Solución de ácido cítrico	*Citric acid*	(UNE-EN ISO 10545-13)	GLA
Solución de hidróxido potásico	*Potasium hidroxide*	(UNE-EN ISO 10545-13)	GLA
Solución de cloruro amónico	*Amonium chloride*	(UNE-EN ISO 10545-13)	GA
Solución de hipoclorito sódico	*Sodium hypochlorite*	(UNE-EN ISO 10545-13)	GA

RESISTENCIA A LAS MANCHAS
RESISTANCE TO STAIN

Agente verde/rojo en aceite ligero	*Green/red agent in light oil*	(UNE-EN ISO 10545-14)	5
Solución de Yodo	*Iodine solution*	(UNE-EN ISO 10545-14)	5
Aceite de oliva	*Olive oil*	(UNE-EN ISO 10545-14)	5

		SI/YES	NO
RESISTENCIA AL CUARTEO ***RESISTANCE TO CRACKING***	(UNE-EN ISO 10545-11)	X	

		SI/YES	NO
ESTABILIDAD DIMENSIONAL Y ASPECTO SUPERFICIAL ***DIMENSIONAL ESTABILITY AND SURFACE ASPECT***	(UNE-EN ISO 10545-2)	X	

		SI/YES	NO
RESISTENCIA AL CHOQUE TÉRMICO ***RESISTANCE TO TERMAL SHOCK***	(UNE-EN ISO 10545-9)	X	

		CLASE / TYPE
RESISTENCIA A LA ABRASIÓN (P.E.I.) ***RESISTANCE TO ABRASION (P.E.I. METHOD)***	(UNE-EN ISO 10545-7)	IV

RESISTENCIA A LA FLEXIÓN ***MODULUS OF RUPTURE***	(UNE-EN ISO 10545-4)	> 45 N/mm^2

		SI/YES	NO
RESISTENCIA A LA HELADA ***FROST RESISTANCE***	(UNE-EN ISO 10545-12)	X	

COEFICIENTE DE ANTIDESLIZAMIENTO ***SLIPNESS COEFFICIENT***	(DIN 51 097)	B	
	(DIN 51 130)	R-10	
	(ASTM C-1028 96)	Fd >0,6	Fw >0,6
	(UNE-ENV 12633/2003)	Clase 1	

ABSORCIÓN DE AGUA ***WATER ABSORPTION***	(UNE-EN ISO 10545-3)	< 0,3 %

(Laboratorio Planta Pavimento)