


KERATILE

| MODELO / MODEL | | BERLIN SERIES | | |
|--|---|--|--|---------------------|
| FOTO / PICTURE (orientative) | |  | | |
| FORMATO / SIZE | | 45X45 cms. | | |
| GRUPO / GROUP | | BIIa | | |
| TIPO / TYPE | | GRES / FLOOR TILE | | |
| DESCRIPCION DEL TEST / TEST DESCRIPTION | | VALOR DEL TEST / TEST VALUE | KERATILE | NORMA / STANDARD |
| ABSORCIÓN DE AGUA / WATER ABSORPTION | | 3%<AA<6% | Cumple / Passed | UNE-EN-ISO 10545-3 |
| FUERZA DE ROTURA / BREAKING STRENGTH | | > 1100 N | Cumple / Passed | UNE-EN-ISO 10545-4 |
| RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION | | > 22 N/mm2 | Cumple / Passed | UNE-EN-ISO 10545-4 |
| ABRASION SUPERFICIAL / SURFACE ABRASION | | Clase / Class | CREMA, GRIS PEI IV MARENGO, BEIGE PEI III | UNE-EN-ISO 10545-7 |
| RESISTENCIA AL CUARTEO / CRACKING RESISTANCE | | Requerido / Requested | Cumple / Passed | UNE-EN-ISO 10545-11 |
| RESISTENCIA A LA HELADA / FROST RESISTANCE | | Metodo Disponible/Available Method | No Aplica/Not Requested | UNE-EN-ISO 10545-12 |
| RESISTENCIA QUIMICA / CHEMICAL RESISTANCE | (PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products) | Mínimo / Minimum GB | Cumple / Passed | UNE-EN-ISO 10545-13 |
| RESISTENCIA A LOS ACIDOS / ACID RESISTANCE | | GHA | Cumple / Passed | UNE-EN-ISO 10545-13 |
| RESISTENCIA A LAS BASES / ALKALINE RESISTANCE | | GHA | Cumple / Passed | UNE-EN-ISO 10545-13 |
| RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS | | Mínimo / Minimum Class 3 | Cumple / Passed | UNE-EN-ISO 10545-14 |
| RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE | | Metodo Disponible / Available Method | Class 1 | UNE-ENV 12633:2003 |
| RESISTENCIA AL RAYADO / HARDNESS (MOHS) | | Mínimo / Minimum 3 | Cumple / Passed | EN 101 |

KERATILE S.L.U.
 CIF B-12943336
 Calle del Ferrocarril, 4
 12593 Moncofa (Castellón) Spain
 Tel. +34 954 584 069 - Fax +34 954 584 070