



INDIC 60x120 R

PORCELÁNICO ESMALTADO / GLAZE PORCELAIN TILE

Indic Grey
KT2021016

Indic Pearl
KT2021017

FORMATO / SIZE

60x120 R / 23''x47''

ACABADO / FINISH

Mate / Matt

GRUPO / GROUP

Bla

TIPO / TYPE

Piedra / Stone



DESCRIPCIÓN DEL TEST / TEST DESCRIPTION		VALOR DEL TEST / TEST VALUE	KTL CERAMICA	NORMA / STANDARD
Absorción de agua / Water absorption		Ev ≤ 0,5%	Cumple / Complies	UNE-EN ISO 10545-3
Fuerza de rotura / Breaking Strength		≥ 1300 N	Cumple / Complies	UNE-EN ISO 10545-4
Resistencia a la flexión / Modulus of rupture		≥ 35 N/mm ²	Cumple / Complies	UNE-EN ISO 10545-4
Abrasion superficial / Surface Abrasion		Clase / Class	PEI 3	UNE-EN-ISO 10545-7
Resistencia al cuarteo / Cracking resistance		Requerido / Requested	Cumple / Complies	UNE-EN ISO 10545-11
Resistencia a la helada / Frost resistance		Requerido / Requested	Cumple / Complies	UNE-EN ISO 10545-12
Resistencia al deslizamiento / Slip resistance		Ángulo crítico de deslizamiento (Rampa) / Critical angle of slip (Inclined platform)	R10	DIN 51130:2014-5
Resistencia química / Chemical resistance	Productos domésticos y de piscina / Household chemicals and swimming pool salts	Mínimo clase B / Minimum class B	Cumple / Complies	UNE-EN ISO 10545-13
	Ácidos a baja concentración / Low concentration of acids	Mínimo clase LB / Minimum class LB	Valor declarado / Declared value	UNE-EN ISO 10545-13
	Bases a baja concentración / Low concentration of alkalis	Mínimo clase LB / Minimum class LB	Valor declarado / Declared value	UNE-EN ISO 10545-13
Resistencia a las manchas / Stain resistance		Mínimo clase 3 / Minimum Class 3	Cumple / Complies	UNE-EN ISO 10545-14