

KERATILE



RN30102023/JJ30102023

MODELO / MODEL	Nanotech SERIE NORDBY MT (WHITE, GREY, NATURAL, HONEY, BROWN)			
FORMATO / SIZE	23 X 120 cms.apprx. RECT.2			
GRUPO / GROUP	Bla			
TIPO / TYPE	PORCELANICO ESMALTADO / Glazed Porcelain Tile			
<u>DESCRIPCION DEL TEST / TEST DESCRIPTION</u>	<u>VALOR DEL TEST / TEST VALUE</u>	KERATILE	<u>NORMA / STANDARD</u>	
ABSORCIÓN DE AGUA / WATER ABSORBTION	AA < 0,5%	Cumple / Passed	UNE-EN-ISO 10545-3	
FUERZA DE ROTURA / BREAKING STRENGTH	> 1300 N	Cumple / Passed	UNE-EN-ISO 10545-4	
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION	> 35 N/mm2	Cumple / Passed	UNE-EN-ISO 10545-4	
ABRASION SUPERFICIAL / SURFACE ABRASION	Clase / Class	PEI IV	UNE-EN-ISO 10545-7	
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE	Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-11	
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE	Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-12	
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Mínimo / Minimum GB	Cumple / Passed	UNE-EN-ISO 10545-13

KERATILE

RESISTENCIA A LOS ACIDOS / ACID RESISTANCE	GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE	GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS	Minimo / Minimum Class 3	Cumple / Passed	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE	Metodo Disponible / Available Method	Clase 3/ Class 3	UNE-ENV 12633:2003
RESISTENCIA AL RAYADO / HARDNESS (MOHS)	Minimo / Minimum 3	Cumple / Passed	EN 101



Brown Nanotech
KT2021019



Grey Nanotech
KT2021018